

APPplay_CARplay & Android Auto set BMW/MINI iDrive CCC (CVBS)



Requirement

| | |
|---------------------------------|---|
| AUDIO OUTPUT | The interface inserts ONLY video signals into the infotainment. It is essential to have an Aux-in, when using audio from the APPplay box |
| VIDEO OUTPUT | Video goes via AV3 |
| CONTROL | You can control APPplay via the original iDrive controller |
| SCREEN | Interface is compatible with iDrive Professional 6.5" & 8.8" |
| OPEN HU | Not need to open the monitor |
| FRONT CAMERA | The front camera input will automatically switch after leaving the reverse gear. You can set the display time in seconds via the OSD menu (1-15 sec). It is also possible to select the FRONT camera input manually |
| OEM REAR CAMERA | The interface does not switch back automatically to the OEM rear camera input when the reverse gear is engaged (<i>with auto gear box</i>). |
| GUIDELINES | Static lines are available via the interface OSD menu |
| iPAS | iPAS option is NOT available |
| PIP | PiP option is available for original parking sensor overlay (Picture in Picture) |
| REAR SELECT CAMERA INPUT | Interface will respond on CAN for cars with auto gearbox. When manual gear box please use the rear detection wire. |
| INSTALLATION | We recommend that the installation will be performed by a qualified specialist |
| EXTRA NOTE | PiP function = split screen iDrive CCC controllers with resistance on the end of the iDrive menu (force feedback") --> APPplay control via iDrive not possible. You must use an external controller. |