

## **Universal duo camera with Sony CCD Duo Lens NTSC**

**Art. Nr:** CAM-UNI-70N

---

### **General:**

This camera is specially designed for universal usage. The inconspicuous, small Duo camera with Sony CCD Duo lens can easily be installed. The camera is completely made out of metal and waterproof according to the IP68 certification level.



### **Features:**

- 1/3" SONY CCD Duo lens
- Specially designed for universal usage
- Lens angle 150°D; 95°H;
- Waterproof according to IP66 certification level

### **Compatible with:**

- Universal usage.

### **The following is provided in the set:**

- Micro Duo camera NTSC
- Installation manual
- Invoice
- Warranty

### **Additional information:**

- With a multimedia interface or video interface it is possible to connect the camera with the original navigation system, ask for the possibilities.

### **Technical features:**

- IP rating: IP66 (Water proof)
- Image Sensors : Colour 1/3"SONY CCD Duo
- IR function
- TV System: NTSC

- Effective Pixels: NTSC 668x576
- Electronic shutter: 1/60 (1/10,000second)
- Horizontal Resolution: 480 TV Line
- Video output: 1Vp-p,75Ohm
- Gamma Consumption: 0.45
- White Balance: Automatic
- Auto Gain Control: Automatic
- Back Light Compensation: Automatic
- S/N Ratio: Better than 48dB
- Lens Angle: 150°D; 95°H; (Degrees)
- Current Consumption: 290 mA
- Power Supply: DC +12V (10%)
- Operating Temperature: -20 C to +70 C
- Storage Temperature : -40 C to +80 C
- Connection: Cinch
- Image: Mirror

**Measurements:**

- Length: mm
- Width: mm