

General:

The NavInc interfaces allow for connecting audio/video sources to activate on the Comand NTG5.0 system. The interface ensures that an input is created on which one external video sources can be connected (e.g. DVD player, DVB-T TV, iPod, etc.).

**Features**

- # Plug and play
- # Activation via AUX option in the Comand menu
- # In combination with Comand NTG5.0
- # Complete with input cables.

The following is provided in the set:

- NavInc interface OBD-MB-NTG5AV
- Installation- and user manual
- Warranty
- Invoice

Extra informatie

- The connected camera must support NTSC video signals
- For only one vehicle, after the programming process the interface stores a unique code of the car. This makes the module unusable for other cars.
- After the first use on a vehicle, this coder is personalized to this vehicle (head-unit) and can be used unlimited (only for this vehicle)

Product specifications:

Voltage supply: 12V DC
Voltage-operating capacity: 10,5 - 14,8 V
Operating current: 48 mA
Power input: 0,70 W
Temperature range: - 30°C up to + 80°C
Weight: 42g
Dimensions W x H x D: 22 x 72 x 50 mm

Automodel:

De interface is geschikt voor de volgende modellen van Mercedes:

| | |
|----------------|-----------|
| C-class (W205) | 2014-201> |
| S-class W222) | 2013-201> |
| GLC-class | 2016-201> |
| V-class | 2015-201> |

Opmerking:

- Alleen in combinatie met Comand NTG5.0
- Niet geschikt voor Comand NTG5.1
- Enkel geschikt voor NTSC bronnen
- Module blijft na gebruik autogebonden.
- 1x activatie mogelijk