

APPplay\_CARplay & Android Auto set BMW/MINI iDrive CCC (CVBS)



Requirement

<b>AUDIO OUTPUT</b>	The interface inserts ONLY video signals into the infotainment. It is essential to have an Aux-in, when using audio from the APPplay box
<b>VIDEO OUTPUT</b>	Video goes via AV3
<b>CONTROL</b>	You can control APPplay via the original iDrive controller
<b>SCREEN</b>	Interface is compatible with iDrive Professional 6.5" & 8.8"
<b>OPEN HU</b>	Not need to open the monitor
<b>FRONT CAMERA</b>	The front camera input will automatically switch after leaving the reverse gear. You can set the display time in seconds via the OSD menu (1-15 sec). It is also possible to select the FRONT camera input manually
<b>OEM REAR CAMERA</b>	The interface does not switch back automatically to the OEM rear camera input when the reverse gear is engaged ( <i>with auto gear box</i> ).
<b>GUIDELINES</b>	Static lines are available via the interface OSD menu
<b>iPAS</b>	iPAS option is NOT available
<b>PIP</b>	PIP option is available for original parking sensor overlay (Picture in Picture)
<b>REAR SELECT CAMERA INPUT</b>	Interface will respond on CAN for cars with auto gearbox. When manual gear box please use the rear detection wire.
<b>INSTALLATION</b>	We recommend that the installation will be performed by a qualified specialist
<b>EXTRA NOTE</b>	PIP function = split screen iDrive CCC controllers with resistance on the end of the iDrive menu (force feedback") --> APPplay control via iDrive not possible. You must use an external controller.